

SB4040S 40A SCRs

FEATURES

● High voltage capacity

● Very high current surge capability

APPLICATIONS

● Line rectifying 50/60 Hz

● Softstart AC motor control

● DC Motor control


● Power converter

● AC power control

● Lighting and temperature control

Parameters Summary

V_{DRM}:1200V, V_{RRM}:1600V, I_T(RMS):40A, I_{2t}:880A, R_{th(j-c)}:0.7~0.8°C/W



ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
Storage junction temperature range	T _{stg}	-40~150	°C
Operating junction temperature range	T _j	-40~125	°C
Repetitive peak off-state voltage	V _{DRM}	1200/1600	V
Repetitive peak reverse voltage	V _{RRM}	1600/1600	V
Non repetitive surge peak Off-state voltage	V _{DSM}	V _{DRM} +100	V
Non repetitive peak reverse voltage	V _{RSM}	V _{RRM} +100	V
Non repetitive surge peak on-state current	I _{TSM}	420	A
RMS On-state current (100° conduction angle)	I _{T(RMS)}	40	A
Average current (180° conduction angle)	I _{T(AV)}	25	A
I ² t value for fusing (tp=10ms)	I ² t	880	A ² S
Critical rate of rise of on-state current (I=2×IGT, tr ≤ 100 ns)	di/dt	150	A/μS
Peak gate current	IGM	4	A
Peak gate power	PGM	5	W

Thermal Resistances

Symbol	Parameter	Value	Unit
R _{th(j-c)}	Junction to case (DC)	1.2 ²	°C/W
	TO-220A	1.2 ²	°C/W
	TO-220C	0.8	°C/W
	TO-3P	0.7	°C/W

Electrical Characteristics (T=25°C unless otherwise specified)	
$I_{C(T)} = 120A$	$V_{DSS} = 1200V$
$V_{GTO} = -2V$	$T_{J(max)} = 140^{\circ}\text{C}$
$I_{DRM} = 60A$	$I_{CRM} = 30A$
$V_{DSS} = 1200V$	$T_{J(min)} = -40^{\circ}\text{C}$
$I_{C(T)} = 120A$	$V_{GTO} = -2V$
$V_{DSS} = 1600V$	$T_{J(max)} = 125^{\circ}\text{C}$
$I_{DRM} = 60A$	$I_{CRM} = 30A$
$V_{DSS} = 1200V$	$T_{J(min)} = -40^{\circ}\text{C}$

Ordering Information	
Symbol	Parameter
V_{GTO}	$I_{TM} = 60A \text{ tp}=380\mu\text{s}$
I_{DRM}	$I_{DRM} = 60A \text{ DRM} = 120A$
I_{CRM}	$I_{CRM} = 30A \text{ CRM} = 60A$

Ordering Information Scheme

SB 40 40 - 12 C S

Standard SCR series

A:TO-220A C:TO-220C
M:TO-3P



VD/VR:1200/1600V

IT(RMS):40A


IGT:40mA

LOGO

TO-220A Package Mechanical Data




TO-220C Package Mechanical Data



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.40		4.60	0.173		0.181
B	0.70		0.90	0.028		0.035
C	0.45		0.60	0.018		0.024
C2	1.30		1.48	0.048		0.052
C3	2.20		2.60	0.087		0.102
D	9.90		10.30	0.385		0.400
E	9.90		10.3	0.390		0.406
F	6.30		6.90	0.248		0.272
G		2.54			0.1	
H	28.0		29.8	1.102		1.173
L1		3.39			0.133	
L2	1.14		1.70	0.045		0.067
L3	2.65		2.95	0.104		0.116
e		3.6			0.142	

TO-3P Package Mechanical Data



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.40		4.60	0.173		0.181
B	1.40		1.60	0.055		0.062
C	15.48		15.88	0.609		0.625
C2	0.50		0.70	0.019		0.027
C3	2.70		2.90	0.106		0.114
D	15.92		16.32	0.626		0.642
E	20.27		20.67	0.799		0.815
F	15.15		15.35	0.590		0.604
G		5.45			0.214	0.216
H	1.10		1.30	0.043		0.051
L1	1.15		1.35	0.045		0.053
L2	2.68		3.08	0.105		0.121
L3		4.20			0.165	
e	4.40		4.60	0.173		0.181

FIG.1 Maximum power dissipation versus on-state current..




FIG.3: Surge peak on-state current versus number of cycles




FIG.5: Non-repetitive surge peak on-state current for a sinusoidal pulse with width $t_p < 10\text{ms}$, and corresponding value of $I_2 t$ ($dI/dt < 50\text{A}/\mu\text{s}$)




FIG.2: on-state current versus case temperature T_c





FIG.4: On-state characteristics (maximum values)



trigger current holding current and latching current versus junction temperature

