



Pin Configuration



SOP-7

Marking Information



SOP-7

DP2701X for product name:

XXXXXX, the first X represents the last year, the second X represents the month, the third and fourth X on behalf of the batch code.

Typical Output Power Table(*)

Output Voltage (V)	Output Current (A)	Output Power (W)
1.2	1.0	1.2
1.5	0.8	1.2
1.8	0.7	1.26
2.1	0.6	1.26
2.4	0.5	1.2
2.7	0.45	1.215
3.0	0.4	1.2
3.3	0.35	1.155
3.6	0.3	1.08
3.9	0.25	0.975
4.2	0.2	0.84
4.5	0.15	0.675
4.8	0.1	0.48
5.1	0.08	0.408
5.4	0.06	0.324
5.7	0.05	0.285
6.0	0.04	0.24
6.3	0.03	0.189
6.6	0.02	0.132
6.9	0.01	0.069
7.2	0.01	0.072
7.5	0.01	0.075
7.8	0.01	0.078
8.1	0.01	0.081
8.4	0.01	0.084
8.7	0.01	0.087
9.0	0.01	0.09
9.3	0.01	0.093
9.6	0.01	0.096
9.9	0.01	0.099
10.2	0.01	0.102
10.5	0.01	0.105
10.8	0.01	0.108
11.1	0.01	0.111
11.4	0.01	0.114
11.7	0.01	0.117
12.0	0.01	0.12

Note 1: The MAX. output power is limited by junction temperature.

XXXXXX

